

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



Time Controls With Enhanced Timing Range
Inventor: William P. Tanguay
Application No. 09/903,368
Attorney Docket No. 99545 (4254-15)

1/9




FIG. 1
PRIOR ART




FIG. 2



Time Controls With Enhanced Timing Range
 Inventor: William P. Tanguay
 Application No. 09/903,368
 Attorney Docket No. 99545 (4254-15)

2/9




FIG. 3a




FIG. 3b



Time Controls With Enhanced Timing Range
Inventor: William P. Tanguay
Application No. 09/903,368
Attorney Docket No. 99545 (4254-15)

4/9




FIG. 4



5/9




FIG. 5




FIG. 6



Time Controls With Enhanced Timing Range
Inventor: William P. Tanguay
Application No. 09/903,368
Attorney Docket No. 99545 (4254-15)

7/9




FIG. 7



Time Controls With Enhanced Timing Range
Inventor: William P. Tanguay
Application No. 09/903,368
Attorney Docket No. 99545 (4254-15)

8/9

TIMEBASE DIAL				
Position	Hours	Minutes	Seconds	Hours
1			15	0.00417
2			30	0.00833
3		1		0.01667
4		2		0.03333
5		3		0.05000
6		4		0.06667
7		5		0.08333
8		6		0.10000
9		8		0.13333
10		10		0.16667
11		15		0.25000
12		20		0.33333
13		25		0.41667
14		30		0.50000
15		40		0.66667
16		45		0.75000
17		50		0.83333
18		60		1.00000
19	1	30		1.50000
20	2	0		2.00000
21	2	30		2.50000
22	3	0		3.00000
23	3	30		3.50000
24	4	0		4.00000
25	6	0		6.00000
26	8	0		8.00000
27	10	0		10.00000
28	12	0		12.00000
29	16	0		16.00000
30	18	0		18.00000
31	20	0		20.00000
32	24	0		24.00000

FIG. 8a



DUTY CYCLE DIAL			
Position	Linear Percentage	Non-linear Percentage ("S" curve)	Logarithmic Percentage
1	0%	0%	0.01%
2	1%	1%	0.12%
3	3%	2%	0.16%
4	7%	3%	0.20%
5	10%	4%	0.24%
6	13%	5%	0.30%
7	17%	8%	0.38%
8	20%	10%	0.48%
9	23%	13%	0.59%
10	27%	15%	0.74%
11	30%	20%	0.93%
12	33%	25%	1.16%
13	37%	30%	1.45%
14	40%	35%	1.81%
15	43%	40%	2.26%
16	47%	50%	2.83%
17	50%	60%	3.53%
18	53%	65%	4.42%
19	57%	70%	5.52%
20	60%	75%	6.90%
21	63%	80%	8.62%
22	67%	85%	10.77%
23	70%	88%	13.46%
24	73%	90%	16.82%
25	77%	93%	21.02%
26	80%	94%	26.26%
27	83%	95%	32.82%
28	87%	96%	41.01%
29	90%	97%	51.25%
30	93%	98%	64.04%
31	97%	99%	80.03%
32	100%	100%	100.00%

FIG. 8b